

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/22/2023

Reviewed on 05/22/2023

**1 Identification****· Product Identifier****· Trade Name: Red Brown Air Dry Phenolic Coating****· Product Number:** Heresite VR-514**· Relevant identified uses of the substance or mixture and uses advised against:****· Product Description:** Red Brown Air Dry Phenolic Primer Finish**· Details of the Supplier of the Safety Data Sheet:****· Manufacturer/Supplier:**

Heresite Protective Coatings, LLC

822 S. 14th Street

Manitowoc, WI 54220, USA

Phone: +1 (920) 684-6646

FAX: +1 (920) 684-0110

peter@heresite.com

**· Emergency telephone number:**

For Chemical Emergency Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

Within USA and Canada: 1-800-424-9300 or Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

**2 Hazard(s) Identification****· Classification of the substance or mixture:**

Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



Health hazard

Germ Cell Mutagenicity 1B

H340 May cause genetic defects.

Carcinogenicity 1A

H350 May cause cancer.

Specific Target Organ Toxicity - Repeated Exposure 1

H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

Aspiration Hazard 1

H304 May be fatal if swallowed and enters airways.



Skin Irritation 2

H315 Causes skin irritation.

Specific Target Organ Toxicity - Single Exposure 3

H335 May cause respiratory irritation.

Aquatic Acute 3

H402 Harmful to aquatic life.

(Contd. on page 2)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/22/2023

Reviewed on 05/22/2023

**Trade Name: Red Brown Air Dry Phenolic Coating****Label elements:****Hazard pictograms:****Signal word:** Danger**Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light aliph.

Limonite

Quartz (SiO<sub>2</sub>)

Distillates (petroleum), hydrotreated light

**Hazard statements:**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H340 May cause genetic defects.

H350 May cause cancer.

H335 May cause respiratory irritation.

H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

H304 May be fatal if swallowed and enters airways.

H402 Harmful to aquatic life.

**Precautionary statements:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

P331 Do NOT induce vomiting.

P302+P352 If on skin: Wash with plenty of water.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P314 Get medical advice/attention if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P370+P378 In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

(Contd. on page 3)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/22/2023

Reviewed on 05/22/2023

**Trade Name: Red Brown Air Dry Phenolic Coating**

P405 Store locked up.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Unknown acute toxicity:**


This value refers to knowledge of known, established toxicological or ecotoxicological values. 14.5 % of the mixture consists of component(s) of unknown toxicity.

· **Classification system:** NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Hazard(s) not otherwise classified (HNOC):** None known

### 3 Composition/Information on Ingredients

· **Chemical characterization: Substance**

· **Description:** Mixture of substances listed below with non-hazardous additions.

· **Dangerous Components:**

CAS: 1317-63-1	Limonite ⚠ Specific Target Organ Toxicity - Single Exposure 3, H335	15-35%
CAS: 64742-89-8	Solvent naphtha (petroleum), light aliph. ⚠ Flammable Liquids 2, H225; ⚠ Germ Cell Mutagenicity 1B, H340; Carcinogenicity 1B, H350; Aspiration Hazard 1, H304	14.470%
CAS: 64742-47-8	Distillates (petroleum), hydrotreated light ⚠ Aspiration Hazard 1, H304; ⚠ Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H336; Flammable Liquids 4, H227	2-12%
CAS: 1317-65-3	Natural limestone ⚠ Specific Target Organ Toxicity - Single Exposure 3, H335	2-12%
CAS: 128-37-0 RTECS: GO 7875000	butylated hydroxytoluene ⚠ Aquatic Acute 1, H400; ⚠ Acute Toxicity - Oral 4, H302	≤2.5%
CAS: 14808-60-7 RTECS: VV 7330000	Quartz (SiO <sub>2</sub> ) ⚠ Carcinogenicity 1A, H350; Specific Target Organ Toxicity - Repeated Exposure 1, H372; ⚠ Acute Toxicity - Inhalation 4, H332; Specific Target Organ Toxicity - Single Exposure 3, H335; Eye Irritation 2B, H320	≤2.5%
CAS: 123-86-4 RTECS: AF 7350000	n-butyl acetate ⚠ Flammable Liquids 3, H226; ⚠ Specific Target Organ Toxicity - Single Exposure 3, H336	≤2.5%

(Contd. on page 4)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/22/2023

Reviewed on 05/22/2023

### Trade Name: Red Brown Air Dry Phenolic Coating

CAS: 64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy <span style="color: red;">⚠</span> Flammable Liquids 3, H226; <span style="color: red;">⚠</span> Germ Cell Mutagenicity 1B, H340; Carcinogenicity 1B, H350; Specific Target Organ Toxicity - Repeated Exposure 1, H372; Aspiration Hazard 1, H304	≤2.5%
CAS: 100-41-4 RTECS: DA 0700000	Ethylbenzene <span style="color: red;">⚠</span> Flammable Liquids 2, H225; <span style="color: red;">⚠</span> Carcinogenicity 2, H351; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304; <span style="color: red;">⚠</span> Acute Toxicity - Inhalation 4, H332	≤2.5%

**Additional information:**

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

### 4 First-Aid Measures

**Description of first aid measures**

**General information:** If symptoms persist, call a physician.

**After inhalation:**

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in the side position for transportation.

**After skin contact:**

Immediately wash with water and soap and rinse thoroughly. If skin irritation occurs, consult a doctor.

**After eye contact:**

If eye irritation occurs, consult a doctor. Rinse opened eye for several minutes under running water.

**After swallowing:**

Never give anything by mouth to an unconscious person. May be harmful if ingested. Can cause respiratory depression and could be fatal. Call a physician or poison control center immediately. Do not induce vomiting without medical advice. To prevent aspiration of swallowed product, lay victim on side with head lower than waist. Seek immediate medical attention.

**Information for doctor**

**Most important symptoms and effects, both acute and delayed:**

Quartz: Can cause silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive; it may lead to disability and death; inhaled from occupational sources is classified as carcinogenic to humans. Some studies show in workers exposed to respirable quartz excess numbers of cases of scleroderma, connective tissue disorders, lupus, rheumatoid arthritis, chronic kidney diseases and end-stage kidney disease, chronic bronchitis and emphysema.

**Indication of any immediate medical attention and special treatment needed:** Treat symptomatically.

### 5 Fire-Fighting Measures

**Extinguishing media**

**Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

**For safety reasons unsuitable extinguishing agents:** Water with full jet

**Special hazards arising from the substance or mixture:** No further relevant information available.

**Advice for firefighters**

**Special protective equipment for firefighters:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

(Contd. on page 5)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/22/2023

Reviewed on 05/22/2023

**Trade Name: Red Brown Air Dry Phenolic Coating**

### 6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures:**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).  
Dispose of contaminated material as waste according to section 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents  
Dispose of the collected material according to regulations.
- **Reference to other sections:**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

· **PAC-1:**

1309-37-1	Iron Oxide (Red)	15 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	0.075 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	5 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	350 mg/m <sup>3</sup>
1330-20-7	Xylene, mixture of isomers	130 ppm
100-41-4	Ethylbenzene	33 ppm

· **PAC-2:**

1309-37-1	Iron Oxide (Red)	360 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	33 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	200 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	1,800 mg/m <sup>3</sup>
1330-20-7	Xylene, mixture of isomers	920* ppm
100-41-4	Ethylbenzene	1100* ppm

· **PAC-3:**

1309-37-1	Iron Oxide (Red)	2,200 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	200 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	3000* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	40,000 mg/m <sup>3</sup>
1330-20-7	Xylene, mixture of isomers	2500* ppm
100-41-4	Ethylbenzene	1800* ppm

### 7 Handling and Storage

- **Handling**
- **Precautions for safe handling:**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.

(Contd. on page 6)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/22/2023

Reviewed on 05/22/2023

**Trade Name: Red Brown Air Dry Phenolic Coating**

Protect from heat.  
 Protect against electrostatic charges.  
 Keep protective respiratory device available.

- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
 Keep receptacle tightly sealed.  
 Store in cool, dry conditions in well sealed receptacles.  
 Protect from heat and direct sunlight.
- **Specific end use(s):** No further relevant information available.

**8 Exposure Controls/Personal Protection**

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters:**
- **Components with occupational exposure limits:**  
 The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
 At this time, the other constituents have no known exposure limits.

<b>64742-47-8 Distillates (petroleum), hydrotreated light</b>	
OSHA PEL	Long-term value: 5 mg/m <sup>3</sup>
<b>1317-65-3 Natural limestone</b>	
NIOSH	Short-term value: 5 mg/m <sup>3</sup> Long-term value: 10 mg/m <sup>3</sup>
NIOSH TWA	Short-term value: 5 mg/m <sup>3</sup> Long-term value: 10 mg/m <sup>3</sup> respirable dust
OSHA	Short-term value: 5 mg/m <sup>3</sup> Long-term value: 15 mg/m <sup>3</sup>
OSHA TWA	Short-term value: 5 mg/m <sup>3</sup> Long-term value: 15 mg/m <sup>3</sup> respirable fraction
<b>128-37-0 butylated hydroxytoluene</b>	
REL	Long-term value: 10 mg/m <sup>3</sup>
TLV	Long-term value: 2* mg/m <sup>3</sup> *as inhalable fraction and vapor, A4
<b>14808-60-7 Quartz (SiO2)</b>	
PEL	Long-term value: 0.05* mg/m <sup>3</sup> *resp. dust; 30mg/m <sup>3</sup> /%SiO <sub>2</sub> +2
REL	Long-term value: 0.05* mg/m <sup>3</sup> *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m <sup>3</sup> *respirable particulate matter, A2
<b>123-86-4 n-butyl acetate</b>	
PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm

(Contd. on page 7)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/22/2023

Reviewed on 05/22/2023

### Trade Name: Red Brown Air Dry Phenolic Coating

REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm
<b>100-41-4 Ethylbenzene</b>	
REL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3

· **Ingredients with biological limit values:**

**100-41-4 Ethylbenzene**

BEI	0.15 g/g creatinine urine end of shift at end of workweek Sum of mandelic acid and phenylglyoxylic acid (nonspecific)
-----	--

· **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

· **Exposure controls:**

· **Personal protective equipment**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.

· **Protection of hands:**



Protective gloves

· **Material of gloves:**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material:**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· **Eye protection:**



Tightly sealed goggles

(Contd. on page 8)



**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/22/2023

Reviewed on 05/22/2023

**Trade Name: Red Brown Air Dry Phenolic Coating****· Body protection:**

Protective work clothing

**· Limitation and supervision of exposure into the environment:**Keep away from drains, surface and ground waters.  
Avoid release into the environment.**\* 9 Physical and Chemical Properties****· Information on basic physical and chemical properties****· General Information****· Appearance:****Form:**

Liquid

**Color:**

Reddish brown

**· Odor:**

Mild aliphatic

**· Odor threshold:**

Not determined.

**· pH-value:**

Not determined.

**· Change in condition****Melting point/Melting range:**

Not determined.

**Boiling point/Boiling range:**

Not determined.

**· Flash point:**

6.7 °C (44.1 °F)

**· Flammability (solid, gaseous):**

Highly flammable.

**· Auto igniting:**

Not applicable

**· Decomposition temperature:**

Not determined.

**· Ignition temperature:**

Product is not self-igniting.

**· Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

**· Explosion limits:****Lower:**

Not determined.

**Upper:**

Not determined.

**· Vapor pressure:**

Not determined.

**· Density @ 20 °C (68 °F):**1.24 g/cm<sup>3</sup> (10.3478 lbs/gal)**· Relative density:**

Not determined.

**· Vapor density:**

Not determined.

**· Evaporation rate:**

Not determined.

**· Solubility in / Miscibility with:****Water:**

Not miscible or difficult to mix.

**· Partition coefficient (n-octanol/water):** Not determined.**· Viscosity:****Dynamic:**

Not determined.

**Kinematic:**

Not determined.

(Contd. on page 9)



## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/22/2023

Reviewed on 05/22/2023

**Trade Name: Red Brown Air Dry Phenolic Coating**

- **Solvent content:**
  - Organic solvents:** 27.17 %
  - VOC content:** 27.17 %
  - 2.83 lb/gal
- **Other information:** No further relevant information available.

**10 Stability and Reactivity**

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Product is stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** Heat, flame and ignition sources.
- **Incompatible materials:** Contact with fluorine, oxygen difluoride, and chlorine trifluoride will cause fire.
- **Hazardous decomposition products:** No dangerous decomposition products known.

**11 Toxicological Information**

- **Information on toxicological effects:**
- **Acute toxicity:**

<b>LD/LC50 values that are relevant for classification:</b>		
<b>64742-47-8 Distillates (petroleum), hydrotreated light</b>		
Oral	LD50	>5,000 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rabbit)
<b>1317-65-3 Natural limestone</b>		
Oral	LD50	6,450 mg/kg (Rat)
<b>128-37-0 butylated hydroxytoluene</b>		
Oral	LD50	890 mg/kg (Rat)
Dermal	LD50	>2,000 mg/kg (Rat)
<b>14808-60-7 Quartz (SiO2)</b>		
Oral	LD50	>22,500 mg/kg (Rat)
		mg/kg (Rabbit)
Inhalative	LC50/96 hours	1,033 mg/l (Trout)
<b>123-86-4 n-butyl acetate</b>		
Oral	LD50	13,100 mg/kg (Rat)
Dermal	LD50	>5,000 mg/kg (Rabbit)
Inhalative	LC50/4 h	>21 mg/l (Rat)
<b>100-41-4 Ethylbenzene</b>		
Oral	LD50	3,500 mg/kg (Rat)
Dermal	LD50	15,433 mg/kg (Rabbit)

- **Primary irritant effect:**
- **On the skin:** Irritant to skin and mucous membranes.
- **On the eye:** No irritating effect.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

(Contd. on page 10)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/22/2023

Reviewed on 05/22/2023

**Trade Name: Red Brown Air Dry Phenolic Coating**

Carcinogenic  
The product can cause inheritable damage.

· **Carcinogenic categories:**

· **IARC (International Agency for Research on Cancer):**

“In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicate dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled”

- Group 1 - Carcinogenic to humans
- Group 2A - Probably carcinogenic to humans
- Group 2B - Possibly carcinogenic to humans
- Group 3 - Not classifiable as to its carcinogenicity to humans
- Group 4 - Probably not carcinogenic to humans

1309-37-1	Iron Oxide (Red)	3
128-37-0	butylated hydroxytoluene	3
14808-60-7	Quartz (SiO <sub>2</sub> )	1
1330-20-7	Xylene, mixture of isomers	3
100-41-4	Ethylbenzene	2B

· **NTP (National Toxicology Program):**

K - Known to be a human carcinogen

14808-60-7	Quartz (SiO <sub>2</sub> )	K
------------	----------------------------	---

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

**12 Ecological Information**

· **Toxicity:**

· **Aquatic toxicity:**

Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.

<b>64742-47-8 Distillates (petroleum), hydrotreated light</b>	
EC50	25 mg/l (Trout) (OECD Test Guideline 203, 96 hour, Static Test)
<b>128-37-0 butylated hydroxytoluene</b>	
EC50	0.42 mg/l (Algae - Selenastrum capricornutum) 0.84 mg/l (Daphnia)
<b>14808-60-7 Quartz (SiO<sub>2</sub>)</b>	
EC50	218 mg/l (Green algae)

(Contd. on page 11)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/22/2023

Reviewed on 05/22/2023

**Trade Name: Red Brown Air Dry Phenolic Coating**

<b>123-86-4 n-butyl acetate</b>	
EC50	51.577 mg/l (Green algae) 17.594 mg/l (Daphnia)
<b>100-41-4 Ethylbenzene</b>	
EC50	4.9 mg/l (Green algae) 1.8-2.4 mg/l (Water flea)

- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 3 (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.  
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment:**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

### 13 Disposal Considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household waste. Do not allow product to reach sewage system.  
Observe all federal, state and local environmental regulations when disposing of this material.
- **Waste disposal key:** US EPA RCRA waste code D001 (ignitability characteristic).
- **Uncleaned packaging**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport Information

- **UN-Number:**
- **DOT, ADR/ADN, IMDG, IATA** UN1263
- **UN proper shipping name:**
- **DOT** Paint
- **ADR/ADN** UN1263 PAINT
- **IMDG, IATA** PAINT
- **Transport hazard class(es):**
- **DOT**



- **Class:** 3 Flammable liquids

(Contd. on page 12)

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/22/2023

Reviewed on 05/22/2023

**Trade Name: Red Brown Air Dry Phenolic Coating**

· **Label:** 3

· **ADR/ADN**



· **Class:** 3 (F1) Flammable liquids  
· **Label:** 3

· **IMDG, IATA**



· **Class:** 3 Flammable liquids  
· **Label:** 3  
· **Packing group:**  
· **DOT, ADR/ADN, IMDG, IATA** II  
· **Environmental hazards:** Not applicable.  
· **Special precautions for user:** Warning: Flammable liquids  
· **Hazard identification number (Kemler code):** 33  
· **EMS Number:** F-E,S-E  
· **Stowage Category** B  
· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.  
· **Transport/Additional information:**  
· **DOT**  
· **Quantity limitations:** On passenger aircraft/rail: 5 L  
On cargo aircraft only: 60 L

· **ADR/ADN**

· **Excepted quantities (EQ):** Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml

· **IMDG**

· **Limited quantities (LQ):** 5L  
· **Excepted quantities (EQ):** Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml  
· **UN "Model Regulation":** UN 1263 PAINT, 3, II

**15 Regulatory Information**

· **Safety, health and environmental regulations/legislation specific for the substance or mixture:**  
· **SARA (Superfund Amendments and Reauthorization):**

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7 Xylene, mixture of isomers

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/22/2023

Reviewed on 05/22/2023

**Trade Name: Red Brown Air Dry Phenolic Coating**

100-41-4	Ethylbenzene
<b>· TSCA (Toxic Substances Control Act):</b>	
All components have the value ACTIVE.	
<b>· Hazardous Air Pollutants</b>	
1330-20-7	Xylene, mixture of isomers
100-41-4	Ethylbenzene

**· California Proposition 65:**



WARNING: This product can expose you to chemicals including [one or more listed chemical] which is [are] known to the State of California to cause cancer [or birth defects or other reproductive harm]. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

<b>· Chemicals known to cause cancer:</b>	
14808-60-7	Quartz (SiO <sub>2</sub> )
100-41-4	Ethylbenzene

<b>· Chemicals known to cause reproductive toxicity for females:</b>	
None of the ingredients are listed.	

<b>· Chemicals known to cause reproductive toxicity for males:</b>	
None of the ingredients are listed.	

<b>· Chemicals known to cause developmental toxicity:</b>	
None of the ingredients are listed.	

<b>· New Jersey Right-to-Know List:</b>	
1317-65-3	Natural limestone
1309-37-1	Iron Oxide (Red)
128-37-0	butylated hydroxytoluene
14808-60-7	Quartz (SiO <sub>2</sub> )
123-86-4	n-butyl acetate
1330-20-7	Xylene, mixture of isomers
100-41-4	Ethylbenzene

<b>· New Jersey Special Hazardous Substance List:</b>		
14808-60-7	Quartz (SiO <sub>2</sub> )	CA
123-86-4	n-butyl acetate	F3
1330-20-7	Xylene, mixture of isomers	F3
100-41-4	Ethylbenzene	CA, F3

<b>· Pennsylvania Right-to-Know List:</b>	
1317-65-3	Natural limestone
1309-37-1	Iron Oxide (Red)
128-37-0	butylated hydroxytoluene
14808-60-7	Quartz (SiO <sub>2</sub> )
123-86-4	n-butyl acetate
1330-20-7	Xylene, mixture of isomers
100-41-4	Ethylbenzene

(Contd. on page 14)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/22/2023

Reviewed on 05/22/2023

**Trade Name: Red Brown Air Dry Phenolic Coating**

· <b>Pennsylvania Special Hazardous Substance List:</b>		
123-86-4	n-butyl acetate	E
1330-20-7	Xylene, mixture of isomers	E
100-41-4	Ethylbenzene	E

· **Carcinogenic categories:**

· <b>EPA (Environmental Protection Agency):</b>		
1330-20-7	Xylene, mixture of isomers	I
100-41-4	Ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH):**

1309-37-1	Iron Oxide (Red)	A4
128-37-0	butylated hydroxytoluene	A4
14808-60-7	Quartz (SiO <sub>2</sub> )	A2
1330-20-7	Xylene, mixture of isomers	A4
100-41-4	Ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health):**

14808-60-7	Quartz (SiO <sub>2</sub> )	
------------	----------------------------	--

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms:**



· **Signal word:** Danger

· **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light aliph.  
Limonite  
Quartz (SiO<sub>2</sub>)  
Distillates (petroleum), hydrotreated light

· **Hazard statements:**

H225 Highly flammable liquid and vapor.  
H315 Causes skin irritation.  
H340 May cause genetic defects.  
H350 May cause cancer.  
H335 May cause respiratory irritation.  
H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.  
H304 May be fatal if swallowed and enters airways.  
H402 Harmful to aquatic life.

· **Precautionary statements:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/22/2023

Reviewed on 05/22/2023

**Trade Name: Red Brown Air Dry Phenolic Coating**

P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P321	Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
P331	Do NOT induce vomiting.
P302+P352	If on skin: Wash with plenty of water.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a poison center/doctor if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P362+P364	Take off contaminated clothing and wash it before reuse.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P370+P378	In case of fire: Use CO <sub>2</sub> , powder or water spray to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

**• National regulations:**

The product is not subject to be labelled according with the prevailing version of the regulations on hazardous substances.

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other Information**

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

**• Contact:****• Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road  
ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety and Health  
OSHA: Occupational Safety & Health Administration  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit

(Contd. on page 16)



## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 05/22/2023

Reviewed on 05/22/2023

### Trade Name: Red Brown Air Dry Phenolic Coating

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Flammable Liquids 3: Flammable liquids – Category 3

Flammable Liquids 4: Flammable liquids – Category 4

Acute Toxicity - Oral 4: Acute toxicity – Category 4

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2B: Serious eye damage/eye irritation – Category 2B

Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B

Carcinogenicity 1A: Carcinogenicity – Category 1A

Carcinogenicity 1B: Carcinogenicity – Category 1B

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) – Category 1

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

Aspiration Hazard 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3

**\* Data compared to the previous version altered.**

SDS created by MSDS Authoring Services [www.msdsauthoring.com](http://www.msdsauthoring.com) +1-877-204-9106