

Safety Data Sheet

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

Product Name: Flat Black Baked Phenolic Coating Product Code: BF-22

MANUFACTURER : Heresite Protective Coatings, LLC
822 S. 14th Street
Manitowoc, WI 54220, USA

TELEPHONE NUMBER: +1 (920) 684-6646

FAX NUMBER: +1 (920) 684-0110

EMERGENCY PHONE: CHEMTREC
+1 (800) 424-9300

E-MAIL ADDRESS OF PERSON RESPONSIBLE:
peter@heresite.com

Product Use: Industrial and Commercial Coatings, primary application to metal.

Not recommended for: Any other application

SECTION 2: HAZARDS IDENTIFICATION

GHS Ratings:

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Oral Toxicity	4	Oral>300+<=2000mg/kg
Dermal Toxicity	3	Dermal>200+<=1000mg/kg
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0 or persistent inflammation
Eye corrosive	1	Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5
Mutagen	1B	Known to produce heritable mutations in human germ cellsSubcategory 1B, Positive results: In vivo heritable germ cell tests in mammals, Human germ cell tests, In vivo somatic mutagenicity tests, combined with some evidence of germ cell mutagenicity
Carcinogen	1A	Known Human Carcinogen Based on human evidence
Reproductive toxin	1A	Based on human evidence

Signal Word: Danger



GHS Hazards

H225	Highly flammable liquid and vapour
H302	Harmful if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H340	May cause genetic defects
H350	May cause cancer
H360	May damage fertility or the unborn child

GHS Precautions

P201	Obtain special instructions before use
------	--

P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/light/equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P264	Wash hands thoroughly after handling
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P310	Immediately call a POISON CENTER or doctor/physician
P321	Specific treatment (see SDS)
P362	Take off contaminated clothing and wash before reuse
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	If exposed or concerned: Get medical advice/attention
P332+P313	If skin irritation occurs: Get medical advice / attention
P370+P378	In case of fire: Use CO ₂ , dry chemical, or foam for extinction.
P405	Store locked up
P403+P235	Store in a well-ventilated place. Keep cool
P501	Dispose of contents/container to in accordance with local/regional/national/international regulations.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
Ethanol	64-17-5	30.00% - 40.00%
Trade Secret	Trade Secret	20.00% - 30.00%
Ethylene Glycol Monobutyl Ether	111-76-2	10.00% - 20.00%
Diatomaceous Earth	68855-54-9	5.00% - 10.00%
Butanol	71-36-3	5.00% - 10.00%
Phenol	108-95-2	1.00% - 5.00%
Xylenes	1330-20-7	1.00% - 5.00%
Carbon Black	1333-86-4	1.00% - 5.00%
Ethyl Benzene	100-41-4	0.10% - 1.00%
Methyl Iso Butyl Ketone	108-10-1	0.10% - 1.00%
Formaldehyde	50-00-0	0.10% - 1.00%

SECTION 4 - FIRST AID MEASURES

General Advice

If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

Inhalation

Remove to fresh air. If breathing has stopped, apply artificial respiration. If breathing is difficult, give oxygen if a qualified operator is available. Get medical attention.

Eye Contact

Immediately flush eyes with large amounts of water for at least 20 minutes, while holding eyelids open. Obtain medical attention immediately, as a precaution.

Skin Contact

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

If person is conscious, give them several glasses of water to drink. Do NOT induce vomiting unless directed to do so by medical personnel. Obtain immediate medical attention.

Most important symptoms and effects, both acute and delayed

No information available

Indication of any immediate medical attention and special treatment needed

Consult a physician

SECTION 5: FIRE-FIGHTING MEASURES
--

Extinguishing Media**Suitable extinguishing media**

Carbon Dioxide, Dry Chemical, Foam

Unsuitable extinguishing media

None identified

Special hazards arising from the substance or mixture

None identified

Advice for firefighters

No data available

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Keep people at a distance and stay on the windward side.

Ensure adequate ventilation.

Keep away from ignition sources.

Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

Prevent from spreading (e.g. by damming-in or oil barriers).

Keep dirty washing solution for appropriate disposal.

Methods and material for containment and cleaning up:

Ensure adequate ventilation and proper training.

Absorb with liquid-binding non combustible material (e.g. sand).

Clean the accident area carefully.

Send for recovery or disposal in suitable containers.

Reference to other sections:

See Section 2, 7, 8 and 13

SECTION 7: HANDLING AND STORAGE
--

Precautions for safe handling:

See Section 2

Conditions for safe storage:

Store in a well-ventilated place.

Keep cool.

Store with only compatible materials.

Specific end uses(s):

See Section 1

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Ethanol 64-17-5	1000 ppm TWA; 1900 mg/m3 TWA	1000 ppm STEL	NIOSH: 1000 ppm TWA; 1900 mg/m3 TWA
Trade Secret Trade Secret	TWA: 1mg/m3 8 hours	TWA: 1mg/m3 8 hours STEL: 3mg/m3 15 minutes	NIOSH REL: TWA: 1mg/m3 10 hours STEL: 3mg/m3 15 minutes
Ethylene Glycol Monobutyl Ether 111-76-2	50 ppm TWA; 240 mg/m3 TWA	20 ppm TWA	NIOSH: 5 ppm TWA; 24 mg/m3 TWA
Diatomaceous Earth 68855-54-9	Table Z-3 Mineral Dusts TWA 20million particles per cubic foot.	Not Established	Not Established
Butanol 71-36-3	100 ppm TWA; 300 mg/m3 TWA	20 ppm TWA	NIOSH: 50 ppm Ceiling; 150 mg/m3 Ceiling
Phenol 108-95-2	5 ppm TWA; 19 mg/m3 TWA	5 ppm TWA	NIOSH: 5 ppm TWA; 19 mg/m3 TWA 15.6 ppm Ceiling (15 min); 60 mg/m3 Ceiling (15 min)
Xylenes 1330-20-7	100 ppm TWA; 435 mg/m3 TWA	150 ppm STEL 100 ppm TWA	Not Established
Carbon Black 1333-86-4	3.5 mg/m3 TWA	3 mg/m3 TWA (inhalable fraction)	NIOSH: 3.5 mg/m3 TWA; 0.1 mg/m3 TWA (Carbon black in presence of Polycyclic aromatic hydrocarbons, as PAH)
Ethyl Benzene 100-41-4	100 ppm TWA; 435 mg/m3 TWA	20 ppm TWA	NIOSH: 100 ppm TWA; 435 mg/m3 TWA 125 ppm STEL; 545 mg/m3 STEL
Methyl Iso Butyl Ketone 108-10-1	100 ppm TWA; 410 mg/m3 TWA	75 ppm STEL 20 ppm TWA	NIOSH: 50 ppm TWA; 205 mg/m3 TWA 75 ppm STEL; 300 mg/m3 STEL
Formaldehyde 50-00-0	0.75 ppm TWA	0.3 ppm Ceiling	NIOSH: 0.016 ppm TWA 0.1 ppm Ceiling (15 min)

Additional information about design of technical systems:

Engineering controls should be used as a primary means to control exposures.

Make available emergency shower and eye wash at the workplace according to appropriate standards.

A workplace risk assessment must be carried out in order to determine the corrective engineering control and organizational measures and personal protective equipment.

No further data; see Section 7.

Exposure controls

Appropriate engineering controls:

No data available

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Take off immediately all contaminated clothing.
 Launder work clothing regularly.
 Wash hands before breaks and at the end of the work .
 Avoid contact with the eyes and skin.
 Do not inhale gases / fumes / aerosols.
 Do not eat, drink or smoke while working to limit potential ingestion of chemicals.

Personal Protective Equipment

Eye and Face Protection:

Wear eye protection/face protection .

Skin Protection:

Wear protective gloves/protective clothing .

Hand Protection:

The glove material has to be impermeable and resistant to the product.

Due to missing tests no recommendation to the glove material can be given for the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation .

Respiratory Protection:

Engineering controls should be used as primary means to control exposures. Local exhaust ventilation is required unless used in a closed system. For laboratory use, handle in a lab fume hood.

If the applicable Occupational Exposure Level (OEL) is exceeded, wear a NIOSH certified respiratory protection equipment meeting US requirements (1910.134 Occupational Safety and Health Administration, Personal Protective Equipment, Respiratory Protection) with a protection factor sufficient to control exposures to below the OEL .

Environmental Exposure Controls:

See Section 6.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<p>Appearance: No Data Found</p> <p>Vapor Pressure: 27.2 mmHg</p> <p>Vapor Density: 2.3</p> <p>Specific Gravity: 1.00</p> <p>Freezing point: No Data Found</p> <p>Boiling range: No Data Found</p> <p>Evaporation rate: No Data Found</p> <p>Explosive Limits: No Data Found</p> <p>Autoignition temperature: No Data Found</p> <p>Viscosity: No Data Found</p>	<p>Odor: No Data Found</p> <p>Odor threshold: No Data Found</p> <p>pH: No Data Found</p> <p>Melting point: No Data Found</p> <p>Solubility: No Data Found</p> <p>Flash point: 54 F, 12 C</p> <p>Flammability: No Data Found</p> <p>Partition coefficient (n-octanol/water): No Data Found</p> <p>Decomposition temperature: No Data Found</p> <p>Grams VOC less water: No Data Found</p>
---	--

SECTION 10: STABILITY AND REACTIVITY

Reactivity:

No known hazards with respect to reactivity when handled and stored according to provisions.

Chemical Stability:

Stable under recommended storage and handling conditions.

Thermal decomposition / conditions to avoid:

Avoid exposure to heat, sources of ignition, and open flame . No decomposition if used according to specifications.

Possibility of hazardous reactions:

No data available.

Conditions to avoid:

High Temperatures.
Heat, flames and sparks.
See section 2.

Incompatible materials:

No further information available.

Strong Oxidizers
Alkali Metals
Ammonia
Peroxides
Heat/sparks/open flames/hot surfaces.
Extremes of temperature and direct sunlight.
Oxidizing agents
Strong bases
Strong Oxidizing Agents
Chlorates
Nitrates
Bases
Strong Acids
Halogens
Hydrogen fluoride
Metals
Heat, sparks, open flames and hot surfaces.

Hazardous decomposition products:

In case of fire: Carbon Dioxide, Carbon Monoxide, Hydrocarbons

SECTION 11: TOXICOLOGICAL INFORMATION**Mixture Toxicity**

Oral Toxicity LD50: 950mg/kg
Dermal Toxicity LD50: 711mg/kg
Inhalation Toxicity LC50: 258mg/L

Component Toxicity

111-76-2	Ethylene Glycol Monobutyl Ether Oral LD50: 470 mg/kg (Rat) Dermal LD50: 99 mg/kg (Rabbit) Inhalation LC50: 307 mg/kg (Rat)
71-36-3	Butanol Oral LD50: 700 mg/kg (Rat) Dermal LD50: 3,402 mg/kg (Rabbit)
108-95-2	Phenol Oral LD50: 340 mg/kg (Rat) Dermal LD50: 630 mg/kg (Rabbit) Inhalation LC50: 900 mg/kg (rat)
1330-20-7	Xylenes Oral LD50: 3,500 mg/kg (Rat) Dermal LD50: 2,000 mg/kg (rabbit) Inhalation LC50: 29 mg/L (Rat)
1333-86-4	Carbon Black Dermal LD50: 3,000 mg/kg (Rabbit)
100-41-4	Ethyl Benzene Oral LD50: 3,500 mg/kg (Rat) Inhalation LC50: 17 mg/L (Rat)
108-10-1	Methyl Iso Butyl Ketone Oral LD50: 2,080 mg/kg (Rat) Dermal LD50: 3,000 mg/kg (Rabbit) Inhalation LC50: 8 mg/L (Rat)
50-00-0	Formaldehyde Oral LD50: 100 mg/kg (Rat) Dermal LD50: 270 mg/kg (Rabbit) Inhalation LC50: 1 mg/L (Rat)

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label.

Routes of Entry:

Inhalation Skin Contact Eye Contact Ingestion

Exposure to this material may affect the following organs:

Blood System Eyes Kidneys Liver Lungs Central Nervous System Auditory System Reproductive System

Effects of Overexposure

May be harmful if inhaled. Causes respiratory tract irritation..

May be harmful if absorbed through skin. Causes skin irritation.

Irritating to eyes.

May be harmful if swallowed

May cause eye irritation.

Inhalation

May be harmful if inhaled. Causes respiratory tract irritation..

Skin Contact

Harmful if absorbed through skin. Causes skin irritation

Eyes

Irritating to eyes.

Ingestion

Harmful if swallowed

Chronic overexposure can cause harm to blood and central nervous system.

Toxic if inhaled.
Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract

Toxic if absorbed through skin. Causes skin burns

Causes eye burns

Toxic if swallowed

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
64-17-5	Ethanol	30 to 40%	Ethanol: IARC: Human carcinogen OSHA: listed
108-10-1	Methyl Iso Butyl Ketone	.1 to 1.0%	Methyl Iso Butyl Ketone: IARC: Possible human carcinogen OSHA: listed

1333-86-4	Carbon Black	1 to 5%	Carbon Black: NIOSH: potential occupational carcinogen IARC: Possible human carcinogen OSHA: listed
100-41-4	Ethyl Benzene	.1 to 1.0%	Ethyl Benzene: IARC: Possible human carcinogen OSHA: listed
50-00-0	Formaldehyde	.1 to 1.0%	Formaldehyde: NIOSH: potential occupational carcinogen IARC: Human carcinogen OSHA: listed

SECTION 12: ECOLOGICAL INFORMATION

Toxicity:

No ecotoxicological data for the substance itself are available.

Persistence and degradability:

No further relevant information available.

Bioaccumulative potential:

No further relevant information available.

Mobility in soil:

No further relevant information available

Results of PBT and VPvB assessment:

No data available

Other adverse effects:

No further relevant information available.

Component Ecotoxicity

Ethanol	96 Hr LC50 <i>Oncorhynchus mykiss</i> : 12.0 - 16.0 mL/L [static]; 96 Hr LC50 <i>Pimephales promelas</i> : >100 mg/L [static]; 96 Hr LC50 <i>Pimephales promelas</i> : 13400 - 15100 mg/L [flow-through] 48 Hr LC50 <i>Daphnia magna</i> : 9268 - 14221 mg/L; 48 Hr EC50 <i>Daphnia magna</i> : 2 mg/L [Static]
Trade Secret	Acute ED50 105 ppm Fresh Water <i>Daphnia</i> - <i>Daphnia magna</i> 48 hours Acute LC50 60 ppm Fresh Water Fish - <i>Lepomis macrochirus</i> 96 hours
Ethylene Glycol Monobutyl Ether	96 Hr LC50 <i>Lepomis macrochirus</i> : 1490 mg/L [static]; 96 Hr LC50 <i>Lepomis macrochirus</i> : 2950 mg/L 48 Hr EC50 <i>Daphnia magna</i> : >1000 mg/L
Diatomaceous Earth	No data available.
Butanol	96 Hr LC50 <i>Pimephales promelas</i> : 1730 - 1910 mg/L [static]; 96 Hr LC50 <i>Pimephales promelas</i> : 1740 mg/L [flow-through]; 96 Hr LC50 <i>Lepomis macrochirus</i> : 100000 - 500000 µg/L [static]; 96 Hr LC50 <i>Pimephales promelas</i> : 1910000 µg/L [static] 48 Hr EC50 <i>Daphnia magna</i> : 1983 mg/L; 48 Hr EC50 <i>Daphnia magna</i> : 1897 - 2072 mg/L [Static] 96 Hr EC50 <i>Desmodesmus subspicatus</i> : >500 mg/L; 72 Hr EC50 <i>Desmodesmus subspicatus</i> : >500 mg/L

Phenol	<p>96 Hr LC50 Pimephales promelas: 11.9 - 50.5 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: 20.5 - 25.6 mg/L [static]; 96 Hr LC50 Pimephales promelas: 32 mg/L; 96 Hr LC50 Oncorhynchus mykiss: 5.449 - 6.789 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 7.5 - 14 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 4.23 - 7.49 mg/L [semi-static]; 96 Hr LC50 Oncorhynchus mykiss: 5.0 - 12.0 mg/L; 96 Hr LC50 Lepomis macrochirus: 13.5 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 11.9 - 25.3 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 11.5 mg/L [semi-static]; 96 Hr LC50 Poecilia reticulata: 34.09 - 47.64 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 31 mg/L [semi-static]; 96 Hr LC50 Brachydanio rerio: 27.8 mg/L; 96 Hr LC50 Cyprinus carpio: 0.00175 mg/L [semi-static]; 96 Hr LC50 Oryzias latipes: 33.9 - 43.3 mg/L [flow-through]; 96 Hr LC50 Oryzias latipes: 23.4 - 36.6 mg/L [static]</p> <p>48 Hr EC50 Daphnia magna: 4.24 - 10.7 mg/L [Static]; 48 Hr EC50 Daphnia magna: 10.2 - 15.5 mg/L</p> <p>96 Hr EC50 Pseudokirchneriella subcapitata: 46.42 mg/L; 96 Hr EC50 Pseudokirchneriella subcapitata: 0.0188 - 0.1044 mg/L [static]; 72 Hr EC50 Desmodemus subspicatus: 187 - 279 mg/L [static]</p>
Xylenes	<p>96 Hr LC50 Pimephales promelas: 13.4 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 2.661 - 4.093 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 13.5 - 17.3 mg/L; 96 Hr LC50 Lepomis macrochirus: 13.1 - 16.5 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 19 mg/L; 96 Hr LC50 Lepomis macrochirus: 7.711 - 9.591 mg/L [static]; 96 Hr LC50 Pimephales promelas: 23.53 - 29.97 mg/L [static]; 96 Hr LC50 Cyprinus carpio: 780 mg/L [semi-static]; 96 Hr LC50 Cyprinus carpio: >780 mg/L; 96 Hr LC50 Poecilia reticulata: 30.26 - 40.75 mg/L [static]</p> <p>48 Hr EC50 water flea: 3.82 mg/L; 48 Hr LC50 Gammarus lacustris: 0.6 mg/L</p>
Carbon Black	<p>LC50-Danio Rerio (Zebra Fish) - 1000mg/l - 96h Daphnia Magna (Water Flea) - 5600mg/l - 24h EC50-Desmodemus Subspicatus - 10000mg/l - 72h</p>
Ethyl Benzene	<p>96 Hr LC50 Oncorhynchus mykiss: 11.0 - 18.0 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 4.2 mg/L [semi-static]; 96 Hr LC50 Pimephales promelas: 7.55 - 11 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 32 mg/L [static]; 96 Hr LC50 Pimephales promelas: 9.1 - 15.6 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 9.6 mg/L [static]</p> <p>48 Hr EC50 Daphnia magna: 1.8 - 2.4 mg/L</p> <p>72 Hr EC50 Pseudokirchneriella subcapitata: 4.6 mg/L; 96 Hr EC50 Pseudokirchneriella subcapitata: >438 mg/L; 72 Hr EC50 Pseudokirchneriella subcapitata: 2.6 - 11.3 mg/L [static]; 96 Hr EC50 Pseudokirchneriella subcapitata: 1.7 - 7.6 mg/L [static]</p>
Methyl Iso Butyl Ketone	<p>96 Hr LC50 Pimephales promelas: 496 - 514 mg/L [flow-through]</p> <p>48 Hr EC50 Daphnia magna: 170 mg/L</p> <p>96 Hr EC50 Pseudokirchneriella subcapitata: 400 mg/L</p>
Formaldehyde	<p>96 Hr LC50 Pimephales promelas: 22.6 - 25.7 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 1510 µg/L [static]; 96 Hr LC50 Brachydanio rerio: 41 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 0.032 - 0.226 mL/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 100 - 136 mg/L [static]; 96 Hr LC50 Pimephales promelas: 23.2 - 29.7 mg/L [static]</p> <p>48 Hr LC50 Daphnia magna: 2 mg/L; 48 Hr EC50 Daphnia magna: 11.3 - 18 mg/L [Static]</p>

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods:

Waste material must be disposed of I/A/W Federal, State & Local environmental control regulations. Incineration is a recommended technology. Empty containers must be handled with care due to product residue. Decontaminate containers prior to disposal. Do not heat/cut empty container with electric or gas torch.

SECTION 14: TRANSPORT INFORMATION

Environmental hazards:

No information available

Special precautions for users:

No information available.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not required, not intended to be carried in bulk tankers.

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
IATA	Paint	1263	II	3
IMDG	Paint	1263	II	3
USDOT	Paint	1263	II	3

SECTION 15: REGULATORY INFORMATION

Classification:

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

50-00-0 Formaldehyde 0.1 to 1.0 %
108-10-1 Methyl Iso Butyl Ketone 0.1 to 1.0 %
100-41-4 Ethyl Benzene 0.1 to 1.0 %
1333-86-4 Carbon Black 1 to 5 %
64-17-5 Ethanol 30 to 40 %

Clean Air Act

50-00-0 Formaldehyde 0.1 to 1.0 %
108-10-1 Methyl Iso Butyl Ketone 0.1 to 1.0 %
100-41-4 Ethyl Benzene 0.1 to 1.0 %
7732-18-5 Water 1 to 5 %
1330-20-7 Xylenes 1 to 5 %
108-95-2 Phenol 1 to 5 %
71-36-3 Butanol 5 to 10 %
111-76-2 Ethylene Glycol Monobutyl Ether 10 to 20 %
64-17-5 Ethanol 30 to 40 %

Clean Water Act

50-00-0 Formaldehyde 0.1 to 1.0 %
100-41-4 Ethyl Benzene 0.1 to 1.0 %
1330-20-7 Xylenes 1 to 5 %
108-95-2 Phenol 1 to 5 %

SARA Section 302

50-00-0
108-10-1
100-41-4
1330-20-7
108-95-2
71-36-3

OSHA Hazards

108-10-1 Methyl Iso Butyl Ketone 0.1 to 1.0 % Carcinogen, Flammable liquid, Target Organ Effect, Irritant
100-41-4 Ethyl Benzene 0.1 to 1.0 % Carcinogen, Flammable liquid
1333-86-4 Carbon Black 1 to 5 % Carcinogen

1330-20-7 Xylenes 1 to 5 % Carcinogen, Flammable liquid, Target Organ Effect, Harmful /skin absorption, Irritant
 108-95-2 Phenol 1 to 5 % Target Organ Effect, Toxic by inhalation, Toxic by ingestion, Mutagen, Corrosive
 71-36-3 Butanol 5 to 10 % Flammable liquid, Target Organ Effect, Irritant
 64-17-5 Ethanol 30 to 40 % Flammable liquid, Target Organ Effect, Irritant

SARA 311/312

50-00-0 Chronic Health Hazard, Acute Health Hazard
 108-10-1 Fire Hazard, Chronic Health Hazard, Acute Health Hazard
 100-41-4 Fire Hazard, Chronic Health Hazard
 1333-86-4 Chronic Health Hazard
 1330-20-7 Fire Hazard, Chronic Health Hazard, Acute Health Hazard
 108-95-2 Chronic Health Hazard, Acute Health Hazard
 71-36-3 Fire Hazard, Chronic Health Hazard, Acute Health Hazard
 111-76-2 Fire Hazard, Chronic Health Hazard, Acute Health Hazard
 64-17-5 Fire Hazard, Chronic Health Hazard, Acute Health Hazard

SARA 313

50-00-0 Formaldehyde 0.1 to 1.0 %
 108-10-1 Methyl Iso Butyl Ketone 0.1 to 1.0 %
 100-41-4 Ethyl Benzene 0.1 to 1.0 %
 1330-20-7 Xylenes 1 to 5 %
 108-95-2 Phenol 1 to 5 %
 71-36-3 Butanol 5 to 10 %

TSCA (Toxic Substance Control Act)

50-00-0 Formaldehyde 0.1 to 1.0 %
 108-10-1 Methyl Iso Butyl Ketone 0.1 to 1.0 %
 100-41-4 Ethyl Benzene 0.1 to 1.0 %
 7732-18-5 Water 1 to 5 %
 108-95-2 Phenol 1 to 5 %
 71-36-3 Butanol 5 to 10 %
 111-76-2 Ethylene Glycol Monobutyl Ether 10 to 20 %

TSCA (Toxic Substance Control Act) 8b

50-00-0 Formaldehyde 0.1 to 1.0 %
 108-10-1 Methyl Iso Butyl Ketone 0.1 to 1.0 %
 100-41-4 Ethyl Benzene 0.1 to 1.0 %
 7732-18-5 Water 1 to 5 %
 1333-86-4 Carbon Black 1 to 5 %
 1330-20-7 Xylenes 1 to 5 %
 108-95-2 Phenol 1 to 5 %
 71-36-3 Butanol 5 to 10 %
 68855-54-9 Diatomaceous Earth 5 to 10 %
 111-76-2 Ethylene Glycol Monobutyl Ether 10 to 20 %
 64-17-5 Ethanol 30 to 40 %

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>
USA	New Jersey Right to Know	No
USA	Pennsylvania Right to Know	No
USA	Massachusetts Right to Know	No
AU	Australia inventory	No
CA	Canadian Domestic Substances List/Non-Domestic Substa	No
EU	European inventory	No
JP	Japan inventory	No
CN	China inventory	No

Korea	Korean Existing and Evaluated Chemical Substances	No
NZ	New Zealand inventory	No
PH	Philippine The Toxic Substances and Hazardous and Nucle	No
Canada		No



EU Risk Phrases

Safety Phrase

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act, and Title 40 of the Code of Federal Regulations part 372.

108-95-2 Phenol 1.0 - 5%
 50-00-0 Formaldehyde 0.1 - 1.0%


SECTION 16: OTHER INFORMATION

Hazardous Material Information System (HMIS)

HEALTH	*	3
FLAMMABILITY		3
PHYSICAL HAZARD		1
PERSONAL PROTECTION	E	

HMIS & NFPA Hazard Rating Legend
 * = Chronic Health Hazard
 0 = INSIGNIFICANT
 1 = SLIGHT
 2 = MODERATE
 3 = HIGH

National Fire Protection Association (NFPA)



DISCLAIMER: The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Date revised: 2016-11-18

Reviewer Revision 2

Date Prepared: 8/24/2021