# **Safety Data Sheet**

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

Product Name: Paint Reducing Solvent for CSE-7200 Series Product Code: S-220

MANUFACTURER: Heresite Protective TELEPHONE NUMBER: +1 (920) 684-6646
Coatings, LLC FAX NUMBER: +1 (920) 684-0110

822 S. 14th Street

Manitowoc, WI 54220, USA

**EMERGENCY PHONE: CHEMTREC** 

+1 (800) 424-9300

E-MAIL ADDRESS OF PERSON RESPONSIBLE:

peter@heresite.com

Product Use: Industrial and Commercial Coatings, primary application to metal.

Not recommended for: Any other application

# **SECTION 2: HAZARDS IDENTIFICATION**

#### **GHS Ratings:**

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)	
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score	
		2.3 < 4.0 or persistent inflammation	
Eye corrosive	2B	Mild eye irritant: Subcategory 2B, Reversible in 7 days	
Carcinogen	2	Limited evidence of human or animal carcinogenicity	
Reproductive toxin	1B	Presumed, Based on experimental animals	
Aspiration hazard	1	Aspiration Toxicity Category 1: Known (regarded)- human	
		evidence - hydrocarbons with kinematic viscosity? 20.5	
		mm2/s at 40° C	

# Signal Word: Danger







# **GHS Hazards**

H225 Highly flammable liquid and vapour

H304 May be fatal if swallowed and enters airways

H315+H320 Causes skin and eye irritation H351 Suspected of causing cancer

H360 May damage fertility or the unborn child

# **GHS Precautions**

SDS for: S-220

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/light/equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P264	Wash hands thoroughly after handling

P280 Wear protective gloves/protective clothing/eye protection/face protection P281 Use personal protective equipment as required P321 Specific treatment (see SDS) P331 Do NOT induce vomiting Take off contaminated clothing and wash before reuse P362 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician P302+P352 IF ON SKIN: Wash with plenty of soap and water. P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 If exposed or concerned: Get medical advice/attention P332+P313 If skin irritation occurs: Get medical advice / attention P337+P313 If eye irritation persists: Get medical advice/attention P370+P378 In case of fire: Use CO2, dry chemical, or foam for extinction.

P405 Store locked up

P403+P235 Store in a well-ventilated place. Keep cool

Dispose of contents/container to in accordance with P501

local/regional/national/international regulations.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
Xylenes	1330-20-7	70.00% - 80.00%
Ethyl Benzene	100-41-4	10.00% - 20.00%

# **SECTION 4 - FIRST AID MEASURES**

#### **General Advice**

If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

# Inhalation

Remove to fresh air. If breathing has stopped, apply artificial respiration. If breathing is difficult, give oxygen if a qualified operator is available. Get medical attention.

# Eye Contact

Immediately flush eyes with large amounts of water for at least 20 minutes, while holding eyelids open. Obtain medical attention immediately, as a precaution.

#### Skin Contact

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

# Ingestion

If person is conscious, give them several glasses of water to drink. Do NOT induce vomiting unless directed to do so by medical personnel. Obtain immediate medical attention.

# Most important symptoms and effects, both acute and delayed

No information available

#### Indication of any immediate medical attention and special treatment needed

Consult a physician

## **SECTION 5: FIRE-FIGHTING MEASURES**

# **Extinguishing Media**

# Suitable extinguishing media

Carbon Dioxide, Dry Chemical, Foam

SDS for: S-220 Page 2 of 8 Printed: 8/11/2021 at 9:58:07AM

#### Unsuitable extinguishing media

None identified

## Special hazards arising from the substance or mixture

None identified

## Advice for firefighters

No data available

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

## Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Keep people at a distance and stay on the windward side.

Ensure adequate ventilation.

Keep away from ignition sources.

#### **Environmental precautions:**

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

Prevent from spreading (e.g. by damming-in or oil barriers).

Keep dirty washing solution for appropriate disposal.

#### Methods and material for containment and cleaning up:

Ensure adequate ventilation and proper training.

Absorb with liquid-binding non combustible material (e.g. sand).

Clean the accident area carefully.

Send for recovery or disposal in suitable containers.

#### Reference to other sections:

See Section 2, 7, 8 and 13

# **SECTION 7: HANDLING AND STORAGE**

## Precautions for safe handling:

See Section 2

# Conditions for safe storage:

Store in a well-ventilated place.

Keep cool.

Store with only compatible materials.

#### Specific end uses(s):

See Section 1

## **SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION**

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Xylenes 1330-20-7	100 ppm TWA; 435 mg/m3 TWA	150 ppm STEL 100 ppm TWA	Not Established
Ethyl Benzene 100-41-4	100 ppm TWA; 435 mg/m3 TWA	20 ppm TWA	NIOSH: 100 ppm TWA; 435 mg/m3 TWA 125 ppm STEL; 545 mg/m3 STEL

# Additional information about design of technical systems:

Engineering controls should be used as a primary means to control exposures.

Make available emergency shower and eye wash at the workplace according to appropriate standards.

A workplace risk assessment must be carried out in order to determine the corrective engineering control and organizational measures and personal protective equipment.

No further data; see Section 7.

SDS for: S-220 Page 3 of 8

## **Exposure controls**

#### Appropriate engineering controls:

No data available

#### General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Take off immediately all contaminated clothing.

Launder work clothing regularly.

Wash hands before breaks and at the end of the work.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

Do not eat, drink or smoke while working to limit potential ingestion of chemicals.

## **Personal Protective Equipment**

#### **Eye and Face Protection:**

Wear eye protection/face protection.

#### **Skin Protection:**

Wear protective gloves/protective clothing.

#### **Hand Protection:**

The glove material has to be impermeable and resistant to the product.

Due to missing tests no recommendation to the glove material can be given for the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

#### **Respiratory Protection:**

Engineering controls should be used as primary means to control exposures. Local exhaust ventilation is required unless used in a closed system. For laboratory use, handle in a lab fume hood.

If the applicable Occupational Exposure Level (OEL) is exceeded, wear a NIOSH certified respiratory protection equipment meeting US requirements (1910.134 Occupational Safety and Health Administration, Personal Protective Equipment, Respiratory Protection) with a protection factor sufficient to control exposures to below the OEL.

# **Environmental Exposure Controls:**

See Section 6.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Appearance: No Data Found

Vapor Pressure: 20.7 mmHg

Vapor Density: 3 7 Specific Gravity 0.87

Freezing point: No Data Found Boiling range: No Data Found

Evaporation rate: No Data Found

Explosive Limits: No Data Found

Autoignition temperature: No Data Found

Viscosity: No Data Found

Odor: No Data Found

Odor threshold: No Data Found

pH: No Data Found

Melting point: No Data Found

Solubility: No Data Found

Flash point: 70 F,21 C

Flammability: No Data Found

Partition coefficient (n- No Data Found

octanol/water):

Decomposition temperature: No Data Found

Grams VOC less water: No Data Found

## **SECTION 10: STABILITY AND REACTIVITY**

SDS for: S-220 Page 4 of 8

Printed: 8/11/2021 at 9:58:07AM

#### Reactivity:

No known hazards with respect to reactivity when handled and stored according to provisions.

#### **Chemical Stability:**

Stable under recommended storage and handling conditions.

#### Thermal decomposition / conditions to avoid:

Avoid exposure to heat, sources of ignition, and open flame. No decomposition if used according to specifications.

#### Possibility of hazardous reactions:

No data available.

#### Conditions to avoid:

High Temperatures.

Heat, flames and sparks.

See section 2.

## Incompatible materials:

No further information available.

Strong Oxidizers

Heat/sparks/open flames/hot surfaces.

#### Hazardous decomposition products:

In case of fire: Carbon Dioxide, Carbon Monoxide, Hydrocarbons

# **SECTION 11: TOXICOLOGICAL INFORMATION**

# **Mixture Toxicity**

Oral Toxicity LD50: 3,500mg/kg Dermal Toxicity LD50: 2,421mg/kg Inhalation Toxicity LC50: 26mg/L

#### **Component Toxicity**

1330-20-7 Xylenes

Oral LD50: 3,500 mg/kg (Rat) Dermal LD50: 2,000 mg/kg (rabbit) Inhalation LC50: 29 mg/L (Rat)

100-41-4 Ethyl Benzene

Oral LD50: 3,500 mg/kg (Rat) Inhalation LC50: 17 mg/L (Rat)

# No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label.

# Routes of Entry:

Inhalation Skin Contact Eye Contact Ingestion

Exposure to this material may affect the following organs:

Blood Eyes Lungs Central Nervous System Skin Respiratory System

**Effects of Overexposure** 

Chronic overexposure can cause harm to blood and central nervous

system.

<u>CAS Number</u> <u>Description</u> <u>% Weight</u> <u>Carcinogen Rating</u>

100-41-4 Ethyl Benzene 10 to 20% Ethyl Benzene: IARC:

Possible human carcinogen OSHA: listed

## **SECTION 12: ECOLOGICAL INFORMATION**

#### Toxicity:

No ecotoxicological data for the substance itself are available.

# Persistence and degradability:

No further relevant information available.

## Bioaccumulative potential:

No further relevant information available.

SDS for: S-220 Page 5 of 8

#### Mobility in soil:

No further relevant information available

#### Results of PBT and VPvB assessment:

No data available

#### Other adverse effects:

No further relevant information available.

## **Component Ecotoxicity**

Xylenes 96 Hr LC50 Pimephales promelas: 13.4 mg/L [flow-through]; 96 Hr LC50

Oncorhynchus mykiss: 2.661 - 4.093 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 13.5 - 17.3 mg/L; 96 Hr LC50 Lepomis macrochirus: 13.1 - 16.5 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 19 mg/L; 96 Hr LC50 Lepomis macrochirus: 7.711 - 9.591 mg/L [static]; 96 Hr LC50 Pimephales promelas: 23.53 - 29.97 mg/L [static]; 96 Hr LC50 Cyprinus carpio: 780 mg/L [semi-static]; 96 Hr LC50 Cyprinus carpio: >780 mg/L; 96 Hr LC50 Poecilia reticulata: 30.26 -

40.75 mg/L [static]

48 Hr EC50 water flea: 3.82 mg/L; 48 Hr LC50 Gammarus lacustris: 0.6 mg/L

Ethyl Benzene 96 Hr LC50 Oncorhynchus mykiss: 11.0 - 18.0 mg/L [static]; 96 Hr LC50

Oncorhynchus mykiss: 4.2 mg/L [semi-static]; 96 Hr LC50 Pimephales

promelas: 7.55 - 11 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 32 mg/L [static]; 96 Hr LC50 Pimephales promelas: 9.1 - 15.6 mg/L [static]; 96 Hr

LC50 Poecilia reticulata: 9.6 mg/L [static] 48 Hr EC50 Daphnia magna: 1.8 - 2.4 mg/L

72 Hr EC50 Pseudokirchneriella subcapitata: 4.6 mg/L; 96 Hr EC50

Pseudokirchneriella subcapitata: >438 mg/L; 72 Hr EC50 Pseudokirchneriella

subcapitata: 2.6 - 11.3 mg/L [static]; 96 Hr EC50 Pseudokirchneriella

subcapitata: 1.7 - 7.6 mg/L [static]

#### SECTION 13: DISPOSAL CONSIDERATIONS

#### Waste treatment methods:

Waste material must be disposed of I/A/W Federal, State & Local environmental control regulations. Incineration is a recommended technology. Empty containers must be handled with care due to product residue. Decontaminate containers prior to disposal. Do not heat/cut empty container with electric or gas torch.

# **SECTION 14: TRANSPORT INFORMATION**

#### **Environmental hazards:**

No information available

#### Special precautions for users:

No information available.

# Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not required, not intended to be carried in bulk tankers.

<b>Agency</b>	Proper Shipping Name	<u>UN Number</u>	Packing Group	<b>Hazard Class</b>
IATA	Xylenes RQ	1307	II	3
IMDG	Xylenes RQ	1307	II	3
USDOT	Xylenes RQ	1307	II	3

## **SECTION 15: REGULATORY INFORMATION**

# Classification:

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

100-41-4 Ethyl Benzene 10 to 20 %

Clean Air Act

SDS for: S-220 Page 6 of 8

100-41-4 Ethyl Benzene 10 to 20 % 1330-20-7 Xylenes 70 to 80 %

# Clean Water Act

100-41-4 Ethyl Benzene 10 to 20 % 1330-20-7 Xylenes 70 to 80 %

## SARA Section 302

100-41-4 1330-20-7

# **OSHA Hazards**

100-41-4 Ethyl Benzene 10 to 20 % Carcinogen, Flammable liquid 1330-20-7 Xylenes 70 to 80 % Carcinogen, Flammable liquid, Target Organ Effect, Harmful /skin absorption, Irritant

- None

## SARA 311/312

100-41-4 Fire Hazard, Chronic Health Hazard 1330-20-7 Fire Hazard, Chronic Health Hazard, Acute Health Hazard

## **SARA 313**

100-41-4 Ethyl Benzene 10 to 20 % 1330-20-7 Xylenes 70 to 80 %

# TSCA (Toxic Substance Control Act)

100-41-4 Ethyl Benzene 10 to 20 %

# TSCA (Toxic Substance Control Act) 8b

100-41-4 Ethyl Benzene 10 to 20 % 1330-20-7 Xylenes 70 to 80 %

Country	Regulation	All Components Listed
USA	New Jersey Right to Know	Yes
USA	Pennsylvania Right to Know	Yes
USA	Massachusetts Right to Know	Yes
AU	Australia inventory	Yes
CA	Canadian Domestic Substances List/Non-Domestic Substa	Yes
EU	European inventory	Yes
JP	Japan inventory	Yes
CN	China inventory	Yes
Korea	Korean Existing and Evaluated Chemical Substances	Yes
NZ	New Zealand inventory	Yes
PH	Philippine The Toxic Substances and Hazardous and Nucle	Yes
Canada		No

# **EU Risk Phrases**

# **Safety Phrase**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act, and Title 40 of the Code of Federal Regulations part 372.

SDS for: S-220 Page 7 of 8

## **SECTION 16: OTHER INFORMATION**

# **Hazardous Material Information System (HMIS)**


#### **HMIS & NFPA Hazard Rating HEALTH** Legend **FLAMMABILITY** \* = Chronic Health Hazard 0 = INSIGNIFICANT PHYSICAL HAZARD

1 = SLIGHT

2 = MODERATE

3 = HIGH

## National Fire Protection Association (NFPA)



DISCLAIMER: The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Reviewer Revision 4 Date revised: 2021-04-26

Date Prepared: 8/11/2021

PERSONAL PROTECTION

SDS for: S-220 Page 8 of 8