Safety Data Sheet

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

Product Name: Paint Reducing Solvent Product Code: S-330

MANUFACTURER: Heresite Protective TELEPHONE NUMBER: +1 (920) 684-6646
Coatings, LLC FAX NUMBER: +1 (920) 684-0110

822 S. 14th Street

Manitowoc, WI 54220, USA EMERGENCY PHONE: CHEMTREC

+1 (800) 424-9300

E-MAIL ADDRESS OF PERSON RESPONSIBLE:

peter@heresite.com

Product Use: Used for thinning of Heresite coatings. Not recommended for: Any other application

SECTION 2: HAZARDS IDENTIFICATION

GHS Ratings:

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Skin corrosive	2 Reversible adverse effects in dermal tissue, Draize s	
		2.3 < 4.0 or persistent inflammation
Eye corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days

Signal Word: Danger





GHS Hazards

H225	Highly flammable liquid and vapour
H303	May be harmful if swallowed
H313	May be harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eve irritation

GHS Precautions

recautions	
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/light/equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P264	Wash hands thoroughly after handling
P280	Wear protective gloves/protective clothing/eye protection/face protection
P321	Specific treatment (see SDS)
P362	Take off contaminated clothing and wash before reuse
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/ shower.

SDS for: S-330 Page 1 of 7

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice / attention P337+P313 If eye irritation persists: Get medical advice/attention

P370+P378 In case of fire: Use CO2, dry chemical, or foam for extinction.

P403+P235 Store in a well-ventilated place. Keep cool

P501 Dispose of contents/container to in accordance with

local/regional/national/international regulations.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS			
Chemical Name	CAS number	Weight Concentration %	
Methyl Ethyl Ketone	78-93-3	90.00% - 100.00%	

SECTION 4 - FIRST AID MEASURES

General Advice

If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

Inhalation

Remove to fresh air. If breathing has stopped, apply artificial respiration. If breathing is difficult, give oxygen if a qualified operator is available. Get medical attention.

Eye Contact

Immediately flush eyes with large amounts of water for at least 20 minutes, while holding eyelids open. Obtain medical attention immediately, as a precaution.

Skin Contact

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

If person is conscious, give them several glasses of water to drink. Do NOT induce vomiting unless directed to do so by medical personnel. Obtain immediate medical attention.

Most important symptoms and effects, both acute and delayed

No information available

Indication of any immediate medical attention and special treatment needed

Consult a physician

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable extinguishing media

Carbon Dioxide, Dry Chemical, Foam

Unsuitable extinguishing media

None identified

Special hazards arising from the substance or mixture

None identified

Advice for firefighters

No data available

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

SDS for: S-330 Page 2 of 7 Printed: 8/10/2021 at 9:49:22AM Keep people at a distance and stay on the windward side.

Ensure adequate ventilation.

Keep away from ignition sources.

Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

Prevent from spreading (e.g. by damming-in or oil barriers).

Keep dirty washing solution for appropriate disposal.

Methods and material for containment and cleaning up:

Ensure adequate ventilation and proper training.

Absorb with liquid-binding non combustible material (e.g. sand).

Clean the accident area carefully.

Send for recovery or disposal in suitable containers.

Reference to other sections:

See Section 2, 7, 8 and 13

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling:

See Section 2

Conditions for safe storage:

Store in a well-ventilated place.

Keep cool.

Store with only compatible materials.

Specific end uses(s):

See Section 1

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION			
Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Methyl Ethyl Ketone 78-93-3	200 ppm TWA; 590 mg/m3 TWA	300 ppm STEL 200 ppm TWA	NIOSH: 200 ppm TWA; 590 mg/m3 TWA
			300 ppm STEL; 885 mg/m3 STEL

Additional information about design of technical systems:

Engineering controls should be used as a primary means to control exposures.

Make available emergency shower and eye wash at the workplace according to appropriate standards.

A workplace risk assessment must be carried out in order to determine the corrective engineering control and organizational measures and personal protective equipment.

No further data; see Section 7.

Exposure controls

Appropriate engineering controls:

No data available

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Take off immediately all contaminated clothing.

Launder work clothing regularly.

Wash hands before breaks and at the end of the work.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

Do not eat, drink or smoke while working to limit potential ingestion of chemicals.

Personal Protective Equipment

SDS for: S-330 Page 3 of 7

Eye and Face Protection:

Wear eye protection/face protection.

Skin Protection:

Wear protective gloves/protective clothing.

Hand Protection:

The glove material has to be impermeable and resistant to the product.

Due to missing tests no recommendation to the glove material can be given for the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation .

Respiratory Protection:

Engineering controls should be used as primary means to control exposures. Local exhaust ventilation is required unless used in a closed system. For laboratory use, handle in a lab fume hood.

If the applicable Occupational Exposure Level (OEL) is exceeded, wear a NIOSH certified respiratory protection equipment meeting US requirements (1910.134 Occupational Safety and Health Administration, Personal Protective Equipment, Respiratory Protection) with a protection factor sufficient to control exposures to below the OEL.

Environmental Exposure Controls:

See Section 6.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: No Data Found

Vapor Pressure: 75.8 mmHg

Vapor Density: 2.4 Specific Gravity 0.81

Freezing point: No Data Found

Boiling range: No Data Found

Evaporation rate: No Data Found

Explosive Limits: No Data Found

Autoignition temperature: No Data Found

Viscosity: No Data Found

Odor: No Data Found

Odor threshold: No Data Found

pH: No Data Found

Melting point: No Data Found

Solubility: No Data Found

Flash point: 16 F,-9 C

Flammability: No Data Found

Partition coefficient (n- No Data Found

octanol/water):

Decomposition temperature: No Data Found

Grams VOC less water: No Data Found

SECTION 10: STABILITY AND REACTIVITY

Reactivity:

No known hazards with respect to reactivity when handled and stored according to provisions.

Chemical Stability:

Stable under recommended storage and handling conditions.

Thermal decomposition / conditions to avoid:

Avoid exposure to heat, sources of ignition, and open flame. No decomposition if used according to specifications.

Possibility of hazardous reactions:

No data available.

Conditions to avoid:

High Temperatures.

Heat, flames and sparks.

See section 2.

Incompatible materials:

No further information available.

SDS for: S-330 Page 4 of 7

Oxidizing agents

Heat, sparks, open flames and hot surfaces.

Hazardous decomposition products:

In case of fire: Carbon Dioxide, Carbon Monoxide, Hydrocarbons

SECTION 11: TOXICOLOGICAL INFORMATION

Mixture Toxicity

Oral Toxicity LD50: 2,483mg/kg Dermal Toxicity LD50: 5,000mg/kg

Component Toxicity

78-93-3 Methyl Ethyl Ketone

Oral LD50: 2,483 mg/kg (Rat) Dermal LD50: 5,000 mg/kg (Rabbit)

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label.

Routes of Entry:

Inhalation

Exposure to this material may affect the following organs:

Eyes Central Nervous System Skin Peripheral Nervous System Respiratory

System

Effects of Overexposure

<u>CAS Number</u> <u>Description</u> <u>% Weight</u> <u>Carcinogen Rating</u>
None No Information Available

SECTION 12: ECOLOGICAL INFORMATION

Toxicity:

No ecotoxicological data for the substance itself are available.

Persistence and degradability:

No further relevant information available.

Bioaccumulative potential:

No further relevant information available.

Mobility in soil:

No further relevant information available

Results of PBT and VPvB assessment:

No data available

Other adverse effects:

No further relevant information available.

Component Ecotoxicity

Methyl Ethyl Ketone 96 Hr LC50 Pimephales promelas: 3130 - 3320 mg/L [flow-through]

48 Hr EC50 Daphnia magna: >520 mg/L; 48 Hr EC50 Daphnia magna: 5091

mg/L; 48 Hr EC50 Daphnia magna: 4025 - 6440 mg/L [Static]

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods:

Waste material must be disposed of I/A/W Federal, State & Local environmental control regulations. Incineration is a recommended technology. Empty containers must be handled with care due to product residue. Decontaminate containers prior to disposal. Do not heat/cut empty container with electric or gas torch.

SECTION 14: TRANSPORT INFORMATION

Environmental hazards:

No information available

Special precautions for users:

No information available.

SDS for: S-330 Page 5 of 7

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not required, not intended to be carried in bulk tankers.

Agency	Proper Shipping Name	<u>UN Number</u>	Packing Group	Hazard Class
IATA	Methyl Ethyl Ketone	1193	II	3
IMDG	Methyl Ethyl Ketone	1193	II	3
USDOT	Methyl Ethyl Ketone	1193	II	3

SECTION 15: REGULATORY INFORMATION

Classification:

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- None

Clean Air Act

78-93-3 Methyl Ethyl Ketone 90 to 100 %

Clean Water Act

- None

SARA Section 302

78-93-3

OSHA Hazards

- None

- None

SARA 311/312

- None

SARA 313

- None

TSCA (Toxic Substance Control Act)

78-93-3 Methyl Ethyl Ketone 90 to 100 %

TSCA (Toxic Substance Control Act) 8b

78-93-3 Methyl Ethyl Ketone 90 to 100 %

Country	Regulation	All Components Listed
USA	New Jersey Right to Know	Yes
USA	Pennsylvania Right to Know	Yes
USA	Massachusetts Right to Know	Yes
AU	Australia inventory	Yes
CA	Canadian Domestic Substances List/Non-Domestic Substa	Yes
EU	European inventory	Yes
JP	Japan inventory	Yes
CN	China inventory	Yes
Korea	Korean Existing and Evaluated Chemical Substances	Yes
NZ	New Zealand inventory	Yes
PH	Philippine The Toxic Substances and Hazardous and Nucle	Yes

Canada



EU Risk Phrases

Safety Phrase

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act, and Title 40 of the Code of Federal Regulations part 372.

SECTION 16: OTHER INFORMATION

Hazardous Material Information System (HMIS)

HEALTH * 2 FLAMMABILITY 3 PHYSICAL HAZARD 0 PERSONAL PROTECTION

HMIS & NFPA Hazard Rating Legend

* = Chronic Health Hazard


0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH

National Fire Protection Association (NFPA)



DISCLAIMER: The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Date revised: 2016-10-07 Reviewer Revision 3

Date Prepared: 8/10/2021

SDS for: S-330

Page 7 of 7