

Safety Data Sheet

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

Product Name: Clear Air Dry Phenolic Coating

Product Code: VR-500F

MANUFACTURER : Heresite Protective Coatings, LLC
822 S. 14th Street
Manitowoc, WI 54220

TELEPHONE NUMBER: 1 (920) 684-6646

FAX NUMBER: 1 (920) 684-0110

EMERGENCY PHONE: CHEMTREC
1 (800) 424-9300

E-MAIL ADDRESS OF PERSON RESPONSIBLE:
peter@heresite.com

Product Use: Industrial and Commercial Coatings, primary application to metal.

Not recommended for: Any other application

SECTION 2: HAZARDS IDENTIFICATION

GHS Ratings:

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0 or persistent inflammation
Eye corrosive	2B	Mild eye irritant: Subcategory 2B, Reversible in 7 days
Skin sensitizer	1	Skin sensitizer
Mutagen	1B	Known to produce heritable mutations in human germ cells Subcategory 1B, Positive results: In vivo heritable germ cell tests in mammals, Human germ cell tests, In vivo somatic mutagenicity tests, combined with some evidence of germ cell mutagenicity
Carcinogen	1B	Presumed Human Carcinogen, Based on demonstrated animal carcinogenicity
Organ toxin single exposure	1	Significant toxicity in humans- Reliable, good quality human case studies or epidemiological studies, Presumed significant toxicity in humans- Animal studies with significant and/or severe toxic effects relevant to humans at generally low exposure (guidanc
Organ toxin repeated exposure	1	Significant toxicity in humans- Reliable, good quality human case studies or epidemiological studies Presumed significant toxicity in humans- Animal studies with significant and/or severe toxic effects relevant to humans at generally low exposure (guidanc
Aspiration hazard	1	Aspiration Toxicity Category 1: Known (regarded)- human evidence - hydrocarbons with kinematic viscosity ? 20.5 mm ² /s at 40° C.

Signal Word: Danger



GHS Hazards

H225 Highly flammable liquid and vapour
H304 May be fatal if swallowed and enters airways
H315 Causes skin irritation
H317 May cause an allergic skin reaction
H340 May cause genetic defects
H350 May cause cancer
H370 Causes damage to organs
H372 Causes damage to organs through prolonged or repeated exposure

GHS Precautions

P201 Obtain special instructions before use
P202 Do not handle until all safety precautions have been read and understood
P210 Keep away from heat/sparks/open flames/hot surfaces No smoking
P233 Keep container tightly closed
P240 Ground/bond container and receiving equipment
P241 Use explosion-proof electrical/ventilating/light/equipment
P242 Use only non-sparking tools
P243 Take precautionary measures against static discharge
P260 Do not breathe dust/fume/gas/mist/vapours/spray
P261 Avoid breathing dust/fume/gas/mist/vapours/spray
P264 Wash hands thoroughly after handling
P270 Do not eat, drink or smoke when using this product
P272 Contaminated work clothing should not be allowed out of the workplace
P280 Wear protective gloves/protective clothing/eye protection/face protection
P281 Use personal protective equipment as required
P314 Get Medical advice/attention if you feel unwell
P321 Specific treatment (see SDS)
P331 Do NOT induce vomiting
P362 Take off contaminated clothing and wash before reuse
P363 Wash contaminated clothing before reuse
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.
Rinse skin with water/ shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P307+P311 IF exposed: Call a POISON CENTER or doctor/physician
P308+P313 If exposed or concerned: Get medical advice/attention
P332+P313 If skin irritation occurs: Get medical advice / attention
P333+P313 If skin irritation or a rash occurs: Get medical advice/attention
P337+P313 If eye irritation persists: Get medical advice/attention
P370+P378 In case of fire: Use CO2, dry chemical, or foam for extinction.
P405 Store locked up
P403+P235 Store in a well-ventilated place. Keep cool
P501 Dispose of contents/container to in accordance with local/regional/national/international regulations.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
VM&P	64742-89-8	20.00% - 30.00%
Mineral Spirits	8052-41-3	10.00% - 20.00%

Hydrotreated Light Distillate (petroleum)	64742-47-8	10.00% - 20.00%
---	------------	-----------------

SECTION 4 - FIRST AID MEASURES

General Advice

If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

Inhalation

Remove to fresh air. If breathing has stopped, apply artificial respiration. If breathing is difficult, give oxygen if a qualified operator is available. Get medical attention.

Eye Contact

Immediately flush eyes with large amounts of water for at least 20 minutes, while holding eyelids open. Obtain medical attention immediately, as a precaution.

Skin Contact

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

If person is conscious, give them several glasses of water to drink. Do NOT induce vomiting unless directed to do so by medical personnel. Obtain immediate medical attention.

Most important symptoms and effects, both acute and delayed

No information available

Indication of any immediate medical attention and special treatment needed

Consult a physician

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable extinguishing media

Carbon Dioxide, Dry Chemical, Foam

Unsuitable extinguishing media

None identified

Special hazards arising from the substance or mixture

None identified

Advice for firefighters

No data available

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Keep people at a distance and stay on the windward side.

Ensure adequate ventilation.

Keep away from ignition sources.

Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

Prevent from spreading (e.g. by damming-in or oil barriers).
Keep dirty washing solution for appropriate disposal.

Methods and material for containment and cleaning up:

Ensure adequate ventilation and proper training.
Absorb with liquid-binding non combustible material (e.g. sand).
Clean the accident area carefully.
Send for recovery or disposal in suitable containers.

Reference to other sections:

See Section 2, 7, 8 and 13

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling:

See Section 2

Conditions for safe storage:

Store in a well-ventilated place.
Keep cool.
Store with only compatible materials.

Specific end uses(s):

See Section 1

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
VM&P 64742-89-8	Z-1A TWA 300ppm /1350 mg/m3	Not Established	Not Established
Mineral Spirits 8052-41-3	500 ppm TWA; 2900 mg/m3 TWA	100 ppm TWA	NIOSH: 350 mg/m3 TWA 1800 mg/m3 Ceiling (15 min)
Hydrotreated Light Distillate (petroleum) 64742-47-8	Not Established	TWA 200 mg/m3 (TLV)	Not Established

Additional information about design of technical systems:

Engineering controls should be used as a primary means to control exposures.
Make available emergency shower and eye wash at the workplace according to appropriate standards.
A workplace risk assessment must be carried out in order to determine the corrective engineering control and organizational measures and personal protective equipment.
No further data; see Section 7.

Exposure controls

Appropriate engineering controls:

No data available

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Take off immediately all contaminated clothing.
Launder work clothing regularly.

Wash hands before breaks and at the end of the work .
 Avoid contact with the eyes and skin.
 Do not inhale gases / fumes / aerosols.
 Do not eat, drink or smoke while working to limit potential ingestion of chemicals.

Personal Protective Equipment

Eye and Face Protection:

Wear eye protection/face protection .

Skin Protection:

Wear protective gloves/protective clothing .

Hand Protection:

The glove material has to be impermeable and resistant to the product.
 Due to missing tests no recommendation to the glove material can be given for the product.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation .

Respiratory Protection:

Engineering controls should be used as primary means to control exposures. Local exhaust ventilation is required unless used in a closed system. For laboratory use, handle in a lab fume hood.
 If the applicable Occupational Exposure Level (OEL) is exceeded, wear a NIOSH certified respiratory protection equipment meeting US requirements (1910.134 Occupational Safety and Health Administration, Personal Protective Equipment, Respiratory Protection) with a protection factor sufficient to control exposures to below the OEL .

Environmental Exposure Controls:

See Section 6.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<p>Appearance: No Data Found</p> <p>Vapor Pressure: 1.4 kPa</p> <p>Vapor Density: 5.1</p> <p>Specific Gravity 0.87</p> <p>Freezing point: No Data Found</p> <p>Boiling range: No Data Found</p> <p>Evaporation rate: No Data Found</p> <p>Explosive Limits: No Data Found</p> <p>Autoignition temperature: No Data Found</p> <p>Viscosity: No Data Found</p>	<p>Odor: No Data Found</p> <p>Odor threshold: No Data Found</p> <p>pH: No Data Found</p> <p>Melting point: No Data Found</p> <p>Solubility: No Data Found</p> <p>Flash point: 14 F,-10 C</p> <p>Flammability: No Data Found</p> <p>Partition coefficient (n- octanol/water): No Data Found</p> <p>Decomposition temperature: No Data Found</p> <p>Grams VOC less water: No Data Found</p>
--	---

SECTION 10: STABILITY AND REACTIVITY

Reactivity:

No known hazards with respect to reactivity when handled and stored according to provisions.

Chemical Stability:

Stable under recommended storage and handling conditions.

Thermal decomposition / conditions to avoid:

Avoid exposure to heat, sources of ignition, and open flame . No decomposition if used according to specifications.

Possibility of hazardous reactions:

No data available.

Conditions to avoid:

High Temperatures.
Heat, flames and sparks.
See section 2.

Incompatible materials:

No further information available.

Hazardous decomposition products:

In case of fire: Carbon Dioxide, Carbon Monoxide, Hydrocarbons

SECTION 11: TOXICOLOGICAL INFORMATION
--

Mixture Toxicity**Component Toxicity**

64742-89-8	VM&P Oral LD50: 5,000 mg/kg (Mouse) Dermal LD50: 3,000 mg/kg (Rabbit) Inhalation LC50: 5,000 ppm
8052-41-3	Mineral Spirits Oral LD50: 5 g/kg (Rat) Dermal LD50: 5 g/kg (Rat)

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label.

Routes of Entry:

Inhalation Ingestion

Exposure to this material may affect the following organs:

Eyes Kidneys Lungs Central Nervous System Skin Respiratory System

Effects of Overexposure

Repeated exposure may cause skin dryness or cracking	Repeated exposure may cause dryness of skin. Repeated exposure may cause dryness of skin.
--	---

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
8052-41-3	Mineral Spirits	10 to 20%	Mineral Spirits: EU REACH: Present (P)
64742-89-8	VM&P	20 to 30%	VM&P: EU REACH: Present (P)

SECTION 12: ECOLOGICAL INFORMATION

Toxicity:

No ecotoxicological data for the substance itself are available.

Persistence and degradability:

No further relevant information available.

Bioaccumulative potential:

No further relevant information available.

Mobility in soil:

No further relevant information available

Results of PBT and VPvB assessment:

No data available

Other adverse effects:

No further relevant information available.

Component Ecotoxicity

VM&P	72 Hr EC50 Pseudokirchneriella subcapitata: 4700 mg/L
Mineral Spirits	Not toxic at limit of solubility LC/EC/IC50 > 1000mg/L Freshwater Fish, Invertebrates and Algae
Hydrotreated Light Distillate (petroleum)	96 Hr LC50 Pimephales promelas: 45 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 2.2 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 2.4 mg/L [static]

SECTION 13: DISPOSAL CONSIDERATIONS
--

Waste treatment methods:

Waste material must be disposed of I/A/W Federal, State & Local environmental control regulations. Incineration is a recommended technology. Empty containers must be handled with care due to product residue. Decontaminate containers prior to disposal. Do not heat/cut empty container with electric or gas torch.

SECTION 14: TRANSPORT INFORMATION
--

Environmental hazards:

No information available

Special precautions for users:

No information available.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not required, not intended to be carried in bulk tankers.

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
IATA	Paint	1263	II	3
IMDG	Paint	1263	II	3
US DOT	Paint	1263	II	3

SECTION 15: REGULATORY INFORMATION

Classification:

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- None

Clean Air Act

- None

SARA Section 302

- None

SARA 311/312

- 64742-47-8 Fire Hazard, Acute Health Hazard
- 64742-89-8 Fire Hazard, Acute Health Hazard

TSCA (Toxic Substance Control Act)

- 64742-47-8 Hydrotreated Light Distillate (petroleum) 10 to 20 %
- 8052-41-3 Mineral Spirits 10 to 20 %
- 64742-89-8 VM&P 20 to 30 %

TSCA (Toxic Substance Control Act) 8b

- 64742-47-8 Hydrotreated Light Distillate (petroleum) 10 to 20 %
- 8052-41-3 Mineral Spirits 10 to 20 %
- 64742-89-8 VM&P 20 to 30 %

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>
USA	New Jersey Right to Know	No
USA	Pennsylvania Right to Know	No
USA	Massachusetts Right to Know	No
AU	Australia inventory	No
CA	Canadian Domestic Substances List/Non-Domestic Substa	No
EU	European inventory	No
JP	Japan inventory	No
CN	China inventory	No
Korea	Korean Existing and Evaluated Chemical Substances	No
NZ	New Zealand inventory	No
PH	Philippine The Toxic Substances and Hazardous and Nucle	No
Canada		No

EU Risk Phrases

Safety Phrase

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act, and Title 40 of the Code of Federal Regulations part 372.


SECTION 16: OTHER INFORMATION

Hazardous Material Information System (HMIS)

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	G

HMIS & NFPA Hazard Rating Legend
 * = Chronic Health Hazard
0 = INSIGNIFICANT
1 = SLIGHT
2 = MODERATE
3 = HIGH

National Fire Protection Association (NFPA)



DISCLAIMER: The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

