

# Safety Data Sheet

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

Product Name: Aluminum Air Dry Phenolic Coating Product Code: VR-507F

**MANUFACTURER : Heresite Protective Coatings, LLC**  
822 S. 14th Street  
Manitowoc, WI 54220, USA

**TELEPHONE NUMBER: +1 (920) 684-6646**

**FAX NUMBER: +1 (920) 684-0110**

**EMERGENCY PHONE: CHEMTREC**  
**+1 (800) 424-9300**

**E-MAIL ADDRESS OF PERSON RESPONSIBLE:**  
**peter@heresite.com**

Product Use: Industrial and Commercial Coatings, primary application to metal.

Not recommended for: Any other application

## SECTION 2: HAZARDS IDENTIFICATION

### GHS Ratings:

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0 or persistent inflammation
Eye corrosive	2B	Mild eye irritant: Subcategory 2B, Reversible in 7 days
Skin sensitizer	1	Skin sensitizer
Mutagen	1B	Known to produce heritable mutations in human germ cellsSubcategory 1B, Positive results: In vivo heritable germ cell tests in mammals, Human germ cell tests, In vivo somatic mutagenicity tests, combined with some evidence of germ cell mutagenicity
Carcinogen	1A	Known Human Carcinogen Based on human evidence
Reproductive toxin	2	Human or animal evidence possibly with other information
Organ toxin single exposure	1	Significant toxicity in humans- Reliable, good quality human case studies or epidemiological studies, Presumed significant toxicity in humans- Animal studies with significant and/or severe toxic effects relevant to humans at generally low exposure (guidan
Aspiration hazard	1	Aspiration Toxicity Category 1: Known (regarded)- human evidence - hydrocarbons with kinematic viscosity ? 20.5 mm2/s at 40° C.

**Signal Word: Danger**



### GHS Hazards

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H340	May cause genetic defects

H350 May cause cancer  
H361 Suspected of damaging fertility or the unborn child  
H370 Causes damage to organs

**GHS Precautions**

P201 Obtain special instructions before use  
P202 Do not handle until all safety precautions have been read and understood  
P210 Keep away from heat/sparks/open flames/hot surfaces No smoking  
P233 Keep container tightly closed  
P240 Ground/bond container and receiving equipment  
P241 Use explosion-proof electrical/ventilating/light/equipment  
P242 Use only non-sparking tools  
P243 Take precautionary measures against static discharge  
P260 Do not breathe dust/fume/gas/mist/vapours/spray  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray  
P264 Wash hands thoroughly after handling  
P270 Do not eat, drink or smoke when using this product  
P272 Contaminated work clothing should not be allowed out of the workplace  
P280 Wear protective gloves/protective clothing/eye protection/face protection  
P281 Use personal protective equipment as required  
P321 Specific treatment (see SDS)  
P331 Do NOT induce vomiting  
P362 Take off contaminated clothing and wash before reuse  
P363 Wash contaminated clothing before reuse  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.  
Rinse skin with water/ shower.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P307+P311 IF exposed: Call a POISON CENTER or doctor/physician  
P308+P313 If exposed or concerned: Get medical advice/attention  
P332+P313 If skin irritation occurs: Get medical advice / attention  
P333+P313 If skin irritation or a rash occurs: Get medical advice/attention  
P337+P313 If eye irritation persists: Get medical advice/attention  
P370+P378 In case of fire: Use CO2, dry chemical, or foam for extinction.  
P405 Store locked up  
P403+P235 Store in a well-ventilated place. Keep cool  
P501 Dispose of contents/container to in accordance with local/regional/national/international regulations.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS number	Weight Concentration %
Hydrotreated Light Distillate (petroleum)	64742-47-8	20.00% - 30.00%
VM&P	64742-89-8	10.00% - 20.00%
Aluminum	7429-90-5	5.00% - 10.00%
Butylated Hydroxytoluene	128-37-0	1.00% - 5.00%
Solvent, Naptha, Heavy Aromatic	64742-95-6	0.10% - 1.00%

**SECTION 4 - FIRST AID MEASURES**

**General Advice**

If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

**Inhalation**

Remove to fresh air. If breathing has stopped, apply artificial respiration. If breathing is difficult, give oxygen if a qualified operator is available. Get medical attention.

**Eye Contact**

Immediately flush eyes with large amounts of water for at least 20 minutes, while holding eyelids open. Obtain medical attention immediately, as a precaution.

**Skin Contact**

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

**Ingestion**

If person is conscious, give them several glasses of water to drink. Do NOT induce vomiting unless directed to do so by medical personnel. Obtain immediate medical attention.

**Most important symptoms and effects, both acute and delayed**

No information available

**Indication of any immediate medical attention and special treatment needed**

Consult a physician

**SECTION 5: FIRE-FIGHTING MEASURES**

**Extinguishing Media**

**Suitable extinguishing media**

Carbon Dioxide, Dry Chemical, Foam

**Unsuitable extinguishing media**

None identified

**Special hazards arising from the substance or mixture**

None identified

**Advice for firefighters**

No data available

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures:**

Wear protective equipment. Keep unprotected persons away.

Keep people at a distance and stay on the windward side.

Ensure adequate ventilation.

Keep away from ignition sources.

**Environmental precautions:**

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

Prevent from spreading (e.g. by damming-in or oil barriers).

Keep dirty washing solution for appropriate disposal.

**Methods and material for containment and cleaning up:**

Ensure adequate ventilation and proper training.

Absorb with liquid-binding non combustible material (e.g. sand).

Clean the accident area carefully.

Send for recovery or disposal in suitable containers.

**Reference to other sections:**

See Section 2, 7, 8 and 13

**SECTION 7: HANDLING AND STORAGE**

**Precautions for safe handling:**

See Section 2

**Conditions for safe storage:**

Store in a well-ventilated place.

Keep cool.

Store with only compatible materials.

**Specific end uses(s):**

See Section 1

**SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION**

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Hydrotreated Light Distillate (petroleum) 64742-47-8	Not Established	TWA 200 mg/m <sup>3</sup> (TLV)	Not Established
VM&P 64742-89-8	Z-1A TWA 300ppm /1350 mg/m <sup>3</sup>	Not Established	Not Established
Aluminum 7429-90-5	15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)	1 mg/m <sup>3</sup> TWA (respirable fraction)	NIOSH: 10 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable dust)
Butylated Hydroxytoluene 128-37-0	Z-1 TWA 10 mg/m <sup>3</sup>	2 mg/m <sup>3</sup> TWA (inhalable fraction and vapor)	NIOSH: 10 mg/m <sup>3</sup> TWA
Solvent, Naptha, Heavy Aromatic 64742-95-6	Not Established	Not Established	Not Established

**Additional information about design of technical systems:**

Engineering controls should be used as a primary means to control exposures.

Make available emergency shower and eye wash at the workplace according to appropriate standards.

A workplace risk assessment must be carried out in order to determine the corrective engineering control and organizational measures and personal protective equipment.

No further data; see Section 7.

**Exposure controls**

**Appropriate engineering controls:**

No data available

**General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Take off immediately all contaminated clothing.

Launder work clothing regularly.

Wash hands before breaks and at the end of the work.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

Do not eat, drink or smoke while working to limit potential ingestion of chemicals.

**Personal Protective Equipment**

**Eye and Face Protection:**

Wear eye protection/face protection.

**Skin Protection:**

Wear protective gloves/protective clothing.

**Hand Protection:**

The glove material has to be impermeable and resistant to the product.

Due to missing tests no recommendation to the glove material can be given for the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

**Respiratory Protection:**

Engineering controls should be used as primary means to control exposures. Local exhaust ventilation is required unless used in a closed system. For laboratory use, handle in a lab fume hood.

If the applicable Occupational Exposure Level (OEL) is exceeded, wear a NIOSH certified respiratory protection equipment meeting US requirements (1910.134 Occupational Safety and Health Administration, Personal Protective Equipment, Respiratory Protection) with a protection factor sufficient to control exposures to below the OEL .

**Environmental Exposure Controls:**

See Section 6.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

<p><b>Appearance:</b> No Data Found</p> <p><b>Vapor Pressure:</b> 0.80 hPa</p> <p><b>Vapor Density:</b> 7.5</p> <p><b>Specific Gravity</b> 0.92</p> <p><b>Freezing point:</b> No Data Found</p> <p><b>Boiling range:</b> No Data Found</p> <p><b>Evaporation rate:</b> No Data Found</p> <p><b>Explosive Limits:</b> No Data Found</p> <p><b>Autoignition temperature:</b> No Data Found</p> <p><b>Viscosity:</b> No Data Found</p>	<p><b>Odor:</b> No Data Found</p> <p><b>Odor threshold:</b> No Data Found</p> <p><b>pH:</b> No Data Found</p> <p><b>Melting point:</b> No Data Found</p> <p><b>Solubility:</b> No Data Found</p> <p><b>Flash point:</b> 14 F,-10 C</p> <p><b>Flammability:</b> No Data Found</p> <p><b>Partition coefficient (n- octanol/water):</b> No Data Found</p> <p><b>Decomposition temperature:</b> No Data Found</p> <p><b>Grams VOC less water:</b> No Data Found</p>
---	---

**SECTION 10: STABILITY AND REACTIVITY**

**Reactivity:**

No known hazards with respect to reactivity when handled and stored according to provisions.

**Chemical Stability:**

Stable under recommended storage and handling conditions.

**Thermal decomposition / conditions to avoid:**

Avoid exposure to heat, sources of ignition, and open flame . No decomposition if used according to specifications.

**Possibility of hazardous reactions:**

No data available.

**Conditions to avoid:**

High Temperatures.

Heat, flames and sparks.

See section 2.

**Incompatible materials:**

No further information available.

Heat/sparks/open flames/hot surfaces.

Strong Oxidizing Agents

Strong Acids

Strong bases

Amines

Heat, sparks, open flames and hot surfaces.

Extremes of temperature and direct sunlight.

Water

Strong Oxidizers

Copper

Brass

Acid Anhydrides  
Bases  
Acid Chlorides

**Hazardous decomposition products:**

In case of fire: Carbon Dioxide, Carbon Monoxide, Hydrocarbons

**SECTION 11: TOXICOLOGICAL INFORMATION**

**Mixture Toxicity**

Oral Toxicity LD50: 4,979mg/kg

**Component Toxicity**

64742-89-8 VM&P  
Oral LD50: 5,000 mg/kg (Mouse) Dermal LD50: 3,000 mg/kg (Rabbit) Inhalation LC50: 5,000 ppm

**No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label.**

**Routes of Entry:**

Ingestion

**Exposure to this material may affect the following organs:**

Eyes Skin Respiratory System

**Effects of Overexposure**

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
64742-95-6	Solvent, Naptha, Heavy Aromatic	.1 to 1.0%	Solvent, Naptha, Heavy Aromatic: EU REACH: Present (P)
64742-89-8	VM&P	10 to 20%	VM&P: EU REACH: Present (P)

**SECTION 12: ECOLOGICAL INFORMATION**

**Toxicity:**

No ecotoxicological data for the substance itself are available.

**Persistence and degradability:**

No further relevant information available.

**Bioaccumulative potential:**

No further relevant information available.

**Mobility in soil:**

No further relevant information available

**Results of PBT and VPvB assessment:**

No data available

**Other adverse effects:**

No further relevant information available.

**Component Ecotoxicity**

Hydrotreated Light Distillate (petroleum)	96 Hr LC50 Pimephales promelas: 45 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 2.2 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 2.4 mg/L [static]
VM&P	72 Hr EC50 Pseudokirchneriella subcapitata: 4700 mg/L
Butylated Hydroxytoluene	72 Hr EC50 Pseudokirchneriella subcapitata: 6 mg/L; 72 Hr EC50 Desmodemus subspicatus: >0.42 mg/L
Solvent, Naptha, Heavy Aromatic	96 Hr LC50 Oncorhynchus mykiss: 9.22 mg/L 48 Hr EC50 Daphnia magna: 6.14 mg/L

## SECTION 13: DISPOSAL CONSIDERATIONS

### Waste treatment methods:

Waste material must be disposed of I/A/W Federal, State & Local environmental control regulations. Incineration is a recommended technology. Empty containers must be handled with care due to product residue. Decontaminate containers prior to disposal. Do not heat/cut empty container with electric or gas torch.

## SECTION 14: TRANSPORT INFORMATION

### Environmental hazards:

No information available

### Special precautions for users:

No information available.

### Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not required, not intended to be carried in bulk tankers.

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
IATA	Paint	1263	II	3
IMDG	Paint	1263	II	3
USDOT	Paint	1263	II	3

## SECTION 15: REGULATORY INFORMATION

### Classification:

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- None

Clean Air Act

- None

Clean Water Act

7429-90-5 Aluminum 5 to 10 %

SARA Section 302

- None

OSHA Hazards

- None

- None

SARA 311/312

64742-95-6 Fire Hazard, Chronic Health Hazard, Acute Health Hazard

128-37-0 Acute Health Hazard

64742-89-8 Fire Hazard, Acute Health Hazard

64742-47-8 Fire Hazard, Acute Health Hazard

SARA 313

7429-90-5 Aluminum 5 to 10 %

TSCA (Toxic Substance Control Act)

64742-95-6 Solvent, Naptha, Heavy Aromatic 0.1 to 1.0 %

7429-90-5 Aluminum 5 to 10 %

64742-89-8 VM&P 10 to 20 %  
 64742-47-8 Hydrotreated Light Distillate (petroleum) 20 to 30 %

**TSCA (Toxic Substance Control Act) 8b**

64742-95-6 Solvent, Naptha, Heavy Aromatic 0.1 to 1.0 %  
 128-37-0 Butylated Hydroxytoluene 1 to 5 %  
 7429-90-5 Aluminum 5 to 10 %  
 64742-89-8 VM&P 10 to 20 %  
 64742-47-8 Hydrotreated Light Distillate (petroleum) 20 to 30 %

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>
USA	New Jersey Right to Know	No
USA	Pennsylvania Right to Know	No
USA	Massachusetts Right to Know	No
AU	Australia inventory	No
CA	Canadian Domestic Substances List/Non-Domestic Substa	No
EU	European inventory	No
JP	Japan inventory	No
CN	China inventory	No
Korea	Korean Existing and Evaluated Chemical Substances	No
NZ	New Zealand inventory	No
PH	Philippine The Toxic Substances and Hazardous and Nucle	No
Canada		No

**EU Risk Phrases**

**Safety Phrase**

**Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA).** This product contains a chemical or chemicals which are subject to the reporting requirements of the Act, and Title 40 of the Code of Federal Regulations part 372.

128-37-0 Butylated Hydroxytoluene 1.0 - 5%


**SECTION 16: OTHER INFORMATION**

**Hazardous Material Information System (HMIS)**

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X

**HMIS & NFPA Hazard Rating Legend**  
 \* = Chronic Health Hazard  
 0 = INSIGNIFICANT  
 1 = SLIGHT  
 2 = MODERATE  
 3 = HIGH

**National Fire Protection Association (NFPA)**



**DISCLAIMER:** The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Date revised: 2016-10-07  
 Date Prepared: 9/29/2021

Reviewer Revision 2